



Outdoor
Sirens

SIR/PLL
SIR/PLSL

P▲R▲DOX HELLAS S.A.

SIR/PLL & SIR/PLSL

Outdoor, Tampering Protected & Battery Back-up Electronic Sirens



The sirens SIR/PLL & SIR/PLSL are designed and manufactured to provide both maximum function abilities and security.

The housing aesthetically pleasant, with build in FLASH and large exterior metal cover made of galvanized steel sheets.

Ensure maximum protection endurance to all weather conditions.

Complies with the requirements of the Directive **89/336/EEC EMC** as amended by directive **93/68/EEC** and the **EN50081-1** and **EN50082-1** Standards.

General Specifications

- Complete initial connection can be made before panel power up. It's put in STANDBY mode only when the + or -SSP command is given.
- The siren is activated when the alarm panel's voltage drops below 9,5V DC.
- Build in FLASH.
- Protection of the siren from short circuit in the electric lamp of the FLASH.
- Protection switch TAMPER from opening or removing from the wall.
- Maximum alarm duration when shut down the SSP.
- Two LEDs indicating siren's proper operation.
- POLYCARBONATE plastic box with UV protection, self extinguishing. Available in white and silver color. FLASH in red, orange and blue color.

Technical Specifications

Operating Voltage	11-14 VDC
Standby Current Drain	10mA
Alarm Current Drain	2,5A
Supported Battery Types	12V 7Ah / 12V 6Ah / 12V 2Ah
Acoustic Pressure	125dB@1m (SIR/PL) 120dB@1m (SIR/PLSL)
Operating Frequency	1600 - 2400 Hz
Alarm Duration	3, 5 or 10 min
Tamper Switch Contact	1A / 12V
Flash Lamp	High Bright LED
Dimensions (HxWxD) [mm]	275x250x90

PARADOX HELLAS S.A.
fire alarm & security systems

3 KORINTHOU str., 144 51 ATHENS GREECE
TEL.: +30 210 28 55 000 FAX: +30 210 28 55 020
www.paradox.gr www.paradoxhellas.eu

