

Exit Buttons

A range of Stainless Steel green domed, push plate and standard architrave exit buttons designed to meet the most robust applications and to comply with Risk Assessment RA001 and EN50133/Industry Codes of Practice. Designs have been made to comply with H&S regulations



XB/PP25



(H: 85mm W: 85mm D: 28mm) for surface mounting

Stainless steel button mounted on a stainless steel plate complete with security screws and innovative green back box

Specification:

Dimensions: S/Steel plate: H:85mm W:85mm
Voltage: <30v DC/AC
Current: 4 Amps @ 30v AC/DC
Operations: > 1 Million
Contacts: NO/NC Contacts
IP Rating: IP 66

XB/SS25



(H: 85mm W: 85mm D: 28mm) for surface mounting

A small push plate mounted on a stainless steel plate complete with security screws and innovative green back box

Specification:

Dimensions: S/Steel plate: H:85mm W:85mm
Voltage: <30v DC/AC
Current: 4 Amps @ 30v AC/DC
Operations: > 1 Million
Contacts: NO/NC Contacts
IP Rating: IP 66

XB/GD25



(H: 85mm W: 85mm D: 28mm) for surface mounting

Green domed button on stainless steel plate complete with security screws and innovative green back box

Specification:

Dimensions: S/Steel plate: H:85mm W:85mm
Voltage: <30v DC/AC
Current: 4 Amps @ 30v AC/DC
Operations: > 1 Million
Contacts: NO/NC Contacts
IP Rating: IP 66

XB/ARCSS25



(H: 85mm W: 39mm D: 28mm) for surface mounting

Stainless steel button mounted on a stainless steel architrave plate complete with screws and innovative green back box

Specification:

Dimensions: S/Steel plate: H:85mm W:39mm
Voltage: <30v DC/AC
Current: 4 Amps @ 30v AC/DC
Operations: > 1 Million
Contacts: NO/NC Contacts
IP Rating: IP 66



Contact us:

Phone:

Tel: +44(0)151 6061000
Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk
Email: info@cqr.co.uk



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

